

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number
WO 2005/017920 A2

(51) International Patent Classification⁷: G21C 13/00

Alfried [ZA/ZA]; 34 Kree Street, Amandasig Ext. 2, 0118 KAREN PARK (ZA).

(21) International Application Number:

PCT/IB2004/001738

(74) Agent: MACKENZIE, Colin; Adams & Adams, Adams & Adams Place, 1140 Prospect Street, Hatfield, PO Box 1014, 0001 Pretoria (ZA).

(22) International Filing Date: 27 May 2004 (27.05.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SI, SZ, TZ, UG, ZM,

(26) Publication Language: English

(30) Priority Data:
2003/6376 15 August 2003 (15.08.2003) ZA


(71) Applicant (for all designated States except US): PEBBLE BED MODULAR REACTOR (PROPRIETARY) LIMITED [ZA/ZA]; 3rd Floor, Lake Buena Vista Building, 1267 Gordon Hood Avenue, 0046 CENTURION (ZA).

(72) Inventor; and

(75) Inventor/Applicant (for US only): FORTIER, Fredrik,

{Continued on next page}

(54) Title: A SUPPORT ARRANGEMENT



(57) Abstract: A nuclear reactor includes a reactor pressure vessel 12 and a core barrel 14, contained within the reactor pressure vessel 12. The reactor 10 further includes a single vertical support 16, for transmitting vertical load from the core barrel to the reactor pressure vessel. Further, lateral support means is provided at an elevation which is above that of the support 16 to provide lateral support to the core barrel 14. This arrangement will result in reduced stress arising from the temperature fluctuations.

WO 2005/017920 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CI, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*